

Model	CPS1500PIE	
Capacity (VA / Watts)	1500VA / 1050W	
Input		
Voltage Range	140Vac – 300Vac	
Frequency Range	45Hz - 65Hz (Auto Sensing)	
DC Input Voltage	24V	
Battery Pack Expansion	Yes	
Output		
Number of Phase	Single Phase	
UPS Outlets (Numbers)	(2) UK type + (1) terminal block or (2) Schuko + (1) terminal block or (2) FR + (1) terminal block	
On Battery Output Voltage	Pure SineWave at 220Vac +/- 5%	
On Battery Output Frequency	50 / 60 Hz +/- 1%	
Over Voltage Protection	Surge to 400V	
Transfer Time	< 10 ms	
Overload Protection*	On Utility: Circuit Breaker	
	On Battery: Internal Current Limiting	
AVR	Double Boost & Single Buck	
Charging Current	20Amps	
Manual Switch mode	Bypass Only	
Surge Protection and Filtering		
Lightning / Surge Protection	Yes	
Physical		
Dimensions(H x W x D)(mm)	325 x 261 x 206	
Weight (kg)	18.6	
Wheels	-	
Status Indicators		
Indicators	Power On	
Audible Alarms	On Battery, Low Battery, Overload	
Multi-function LCD Readout	Yes	
Communication		
PowerPanel® Software	-	
Management		
Connectivity Ports	-	
SNMP/HTTP Capable	-	
*FR/Schuko/UK sockets available		

