

Model	CPS5000PRO
Capacity (VA / Watts)	5000VA / 3500W
Input	
Voltage Range	140Vac – 300Vac
Frequency Range	45Hz - 65Hz (Auto Sensing)
DC Input Voltage	48V
Battery Pack Expansion	Yes
Output	
Number of Phase	Single Phase
UPS Outlets (Numbers)	(2) UK type + (1) terminal block or (2) Schuko + (1) terminal block or (2) FR + (1) terminal block
On Battery Output Voltage	Pure SineWave at 220Vac +/- 5%
On Battery Output Frequency	50 / 60 Hz +/- 1%
Over Voltage Protection	Surge to 400V
Transfer Time	< 10 ms
Overload Protection*	On Utility: Circuit Breaker On Battery: Internal Current Limiting
AVR	Boost& Buck
Charging Current	45Amps
Manual Switch mode	Normal / Bypass with AVR / Bypass / Off
Surge Protection and Filtering	
Lightning / Surge Protection	Yes
Physical	
Dimensions(H x W x D)(mm)	440 x 330 x 260
Weight (kg)	45
Wheels	Yes
Status Indicators	
Indicators	Power On
Audible Alarms	On Battery, Low Battery, Overload
Multi-function LCD Readout	Yes
Communication	
PowerPanel® Software	Yes
Management	
Connectivity Ports	Yes, with optional USB or Serial or SNMP Card
SNMP/HTTP Capable	Yes