

| | |
|---------------------------------------|---------------------------------------|
| Model | CPS600E |
| Capacity (VA / Watts) | 600VA / 420W |
| Input | |
| Voltage Range | 140Vac - 300Vac |
| Frequency Range | 45Hz - 65Hz (Auto Sensing) |
| DC Input Voltage | 12V |
| Battery Pack Expansion | - |
| Output | |
| Number of Phase | Single Phase |
| UPS Outlets (Numbers) | (1) Schuko or (1)FR |
| On Battery Output Voltage | Pure SineWave* at 220Vac +/- 5% |
| On Battery Output Frequency | 50 / 60 Hz +/- 1% |
| Over Voltage Protection | Surge to 400V |
| Transfer Time | < 10 ms |
| Overload Protection* | On Utility: Fuse |
| | On Battery: Internal Current Limiting |
| AVR | Single Boost & Single Buck |
| Charging Current | 10Amps |
| Manual Switch mode | - |
| Surge Protection and Filtering | |
| Lightning / Surge Protection | Yes |
| Physical | |
| Dimensions(H x W x D)(mm) | 162 x 240 x 90 |
| Weight (kg) | 4.1 |
| Wheels | - |
| Status Indicators | |
| Indicators | Power On |
| Audible Alarms | On Battery, Low Battery, Overload |
| Multi-function LCD Readout | Yes |
| Communication | |
| PowerPanelR Software | - |
| Management | |
| Connectivity Ports | - |
| SNMP/HTTP Capable | - |